## 16X9 INC. CINE LENS MOUNT



#### Features

- Works with virtually all PL-mount lenses
- 1/4"-20 Thread for use with Rod Supports
- Back Focus Adjustments with use of Shims
- Designed from Aluminum & Stainelss Steel
- Added Support with the 15mm Mini Rod Support Bracket
- Accepts 3rd-Party 15mm Mini Rod Support
- Brackets

### Model Numbers

- For Sony E-mount to PL with 15mm Lens Support [169-CLM-PLE-S]
- For Sony E-mount to PL (15mm Lens Support Not Included) [169-CLM-PLE]
- For Micro 4/3-mount to PL with 15mm Lens Support [169-CLM-PLMF-S]
- For Micro 4/3-mount to PL (15mm Lens Support Not Included) [169-CLM-PLMF]
- 15mm Lens Bracket [169-CLM-LS15]







# Cine-style Characteristics. A Reality with the Cine Lens Mount.

#### PL-Mount Adapter

Getting cinema lens characteristics on Micro 4/3" & Emount cameras is now a reality with the introduction of the 16x9 Inc. PL-Mount adapter from 16x9 Inc for PLmount cine lenses. The adapter works with any Micro 4/3" sensor camera, as well as with Sony's E-mount cameras that features an S35 APS-size sensor. Not to be left out, mirrorless cameras such as dSLRs can take advantage of the PL-Mount adapter.

> Designed from aluminum and stainless steel, the 16x9 Inc. PL-Mount adapter features front and rear bayonet locking mechanisms. 16x9 Inc. offers an

optional 15mm mini rod support bracket, and the PL-Mount adapter also accepts thirdparty 15mm mini rod support brackets.

The PL-Mount adapter comes preset to the appropriate flange focus depths for back focus. However, when a minor adjustment may be required due to non-calibrated lenses, inserting or removing sized shims allows you to adjust the total mount depth depending on how far off the lens is to its markings. For best accuracy, this is done with the PL-Mount on the camera with lens and using a professionalgrade back-focus chart. The shims are interchanged by removing the back mount, which adapts the PL mount body to the actual camera and is held in place by six screws. Removing the back mount exposes the already-inserted shims. Just add or remove shims based on the non-calibrated lens needs.

The 16x9 Inc. PL-Mount works with virtually all PL-mount lenses.

