

Q5 Color LED Fresnel

(P/N: FLXQ5CLR)

Description

The Q5 Color is a 185W 5" LED Fresnel that generates high-quality RGBW light output. This fixture uses the latest iteration of Fiilex's Dense Matrix LED technology to deliver color quality and optical versatility that are superior to previous generations of LED fresnels. With its wide spot/flood range, smooth dimming to 0%, no flicker, and high CRI, the Q5 Color combines the extensive feature set of top-tier RGBW LEDs with the performance of a tungsten fresnel.

The Q5 light head weighs only 7 lbs, and its innovative V-mount power system means that the fixture's power supply can be easily swapped out with compatible V-mount batteries. Light settings can be adjusted on the Q5's back panel via the directional pad or the intuitive control knobs. The directional pad can also access the Q5's different fan and dimming modes, as well as the various control modes, which include CCT, HSI, Gels, and Effects in both 8-bit and 16-bit versions.

Features

- High-CRI white light output (2000-10000K)
- Additional 8 and 16 bit color modes: RGBW, Effects, HSI, Gel Presets, CCT + RGBW, etc.)
- 12-55° spot/flood range with no optical aberrations
- Barndoor cuts clean with no color splitting
- Dims down to 0% without flicker or color shift
- V-mount power supply swaps easily with 26V batteries
- Extremely lightweight (≈7 lbs)
- Removable fresnel for wider throw / softbox compatibility
- Smooth and Sharp dimming modes
- Three fan speed modes: Full, Variable, Silent
- IP-24 Rating (Water-Resistant)

Accessories

- FLXA039 - 5" Speed Ring
- FLXA049 - Medium Softbox w/ 5" Speed Ring
- FLXA054 - Medium Softbox
- FLXA059 - Grid for Medium Softbox
- [Other manufacturer softbox compatibility](#)

Specifications

Fresnel Diameter	5"
Beam Angle	12°-55° (80° without fresnel)
CCT Range	2800-10000K continuous tuning + magenta/green shift
CRI	95 typical
Control Modes	RGBW, CCT, HSI, Gel Presets, Effects, CCT + RGBW, CCT + HSI, CIE XY
Dimming	100 - 0%
Dimming Modes	Smooth, Sharp

Light Engine	1x 165W DiCon Dense Matrix LED
Power Consumption	185W AC 165W DC
DC Input	24-48V DC
AC Input	100-240V AC, 50 - 60Hz
Power Port	XLR-3
DMX Port	XLR-5
Weight	Fixture: 7.3 lbs / 3.3 kg Power Supply: 2.6 lbs / 1.2 kg
Dimensions	11.1" x 7.2" x 13.2" / 28.3cm x 18.2cm x 33.6cm
Mount Type	Combo (baby stud female / junior stud male)
IP Rating	IP-24 (water-resistant)
Thermal Design	Aluminum extrusion cooling system w/ fan
Operating Temperature	0-40° C / 32-104°F
Photometrics / CRT Data	LINK

Items Included

- (1) Q5 Color Light Head
- (1) Power Supply
- (1) 5" Barndoor